TECHNICAL DATA SHEET



600WB Film Unroller

Product data		
~ construction ~ maximum film roll width ~ height ~ length ~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width	Product description	
~ construction ~ maximum film roll width ~ height ~ length ~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width		
~ construction ~ maximum film roll width ~ height ~ length ~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width		
~ maximum film roll width ~ height ~ length ~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width	Product data	
~ height ~ length ~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width	~ construction	
~ length ~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width	~ maximum film roll width	
~ length ~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width	~ height	
~ width ~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width		
~ weight Packaging data ~ units per case ~ case height ~ case length ~ case width	-	
Packaging data ~ units per case ~ case height ~ case length ~ case width		
~ units per case ~ case height ~ case length ~ case width		
~ units per case ~ case height ~ case length ~ case width	Packagina data	
~ case height ~ case length ~ case width		
~ case length ~ case width		
~ case width		
	~ case weight	

Holds and dispenses plastic shrink film and layflat tubing Integral separator bar for folded shrink film

Powder coated steel frame, aluminium rollers

600mm

84mm

680mm

196mm

2.8kg

6

270mm

695mm

416mm

18.32kg

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.