

AS400

SIDE SEALING SEMI-AUTO STRAPPING MACHINE



Side sealing configuration and stainless steel cabinet designed for use in harsh and corrosive environments.





AS400

SIDE SEALING SEMI-AUTO STRAPPING MACHINE

Based on the reliable TMS300, this machine features a side sealing configuration and stainless steel cabinet that prevent water or debris from the pack damaging the mechanism and protect against harsh and corrosive environments.

Features include:

- > Stainless steel construction
- > Adjustable table height 420mm - 770mm
- > Braking swivel castors
- > Reliable, energy efficient operation
- > Simple use and maintenance



- | | |
|---|--|
| Suitable for use with polypropylene strapping | Strapping tension range |
| Strapping speed/cycle rate | Power requirements |
| Heat weld seal - no need for metal seals | Suitable for engineering industry applications |
| Suitable for carton strapping applications | Total machine weight |
| Suitable for food industry applications | Adjustable leg/table height |



Roller table

Simple to use electronic control panel



Adjustable table height

Specifications

Machine Weight:	125 kg
Machine Dims w x d x h (mm):	675 x 1045 x 1625
Max Package Weight:	120 kg
Strap Widths (mm):	9-16
Min/Max PP Thickness:	0.5mm - 0.75mm
Min/Max Tension:	15-45 kg (Strap Dependent)
Speed/Cycle:	3 secs (@50Hz if applicable)
Power Requirement:	240v 50Hz
Power Consumption:	250w

Options

- > Adjustable cooling time (0-2 sec.)

