

Slipguard® ASL0812-10 Anti-slip Sheets

Product description	FSC recycled paper with an aqueous, residue-free coating that when used as an interlayer on palletised goods, increases pallet load stability
Product features	<ul style="list-style-type: none"> ~ high non-slip properties ~ easy to use ~ reusable ~ 100% recyclable with ISO 14062 ecodesign certification ~ suitable as tertiary packaging and for indirect food contact use ~ standard pallet sizes from stock ~ custom sizes and weights to order
Product data	
~ standard paper weight	100gsm
~ dimensions	800 x 1200mm
Technical data	
~ slide angle (NF Q 03-083)	<ul style="list-style-type: none"> ≥ 55° (contact between sheets of Anti Slip Paper) ≥ 42° (contact between Anti Slip Paper and flat paper/cardboard surfaces)
~ coefficient of friction	
~ static (ISO 8295)	<ul style="list-style-type: none"> ≥ 1.4 (contact between sheets of Anti Slip Paper) ≥ 0.9 (contact between Anti Slip Paper and flat paper/cardboard surfaces)
~ dynamic (ISO 8295)	<ul style="list-style-type: none"> ≥ 1.0 (contact between sheets of Anti Slip Paper) ≥ 0.7 (contact between Anti Slip Paper and flat paper/cardboard surfaces)
Optimal storage/usage	
~ storage (temperature)	0°C to + 40°C
~ storage (humidity)	50% RH
~ storage (light)	prolonged exposure to sunlight may cause discolouration
~ usage	best used within 6 months
Packaging data	
~ box quantity	200 sheets
~ pallet quantity	5,000 sheets bulk packed

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.