## TECHNICAL DATA SHEET



## **BBP48** Polypropylene Tape

Product description	Low-noise polypropylene tape for price-sensitive applications
Product data	
~ film	Bi-axial oriented polypropylene film (BOPP)
~ film thickness	25mu (ASTMD 3652)
~ adhesive	Pressure-sensitive water based acrylic
~ adhesive thickness	20gsm within acceptable tolerance of +/-6% (ASTMD 3652)
~ colour	Buff
~ roll width	48mm
~ roll length	66mtr
Technical data	
~ initial tack	3.5cm (ASTMD-3121M)
~ peeling adhesion	2.6N/cm (ASTMD-3330M)
~ shear value on steel	>24 hours (ASTMD-3654M)
~ tensile strength	51N/cm (ASTMD-3759)
~ elongation at break	140% (ASTMD-3759)
<b>J</b>	
Storage and use	
~ optimum storage	Maximum 6 months in original packaging and ambient conditions
	of +22°C and 50% RH
	Protect from extreme temperatures, humidity and direct sunlight
~ optimum usage	Ambient temperature of +18°C
Packaging data	
~ rolls per case	36
~ case weight	5.6kg

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.