

TECHNICAL DATA SHEET



BCP75 Polypropylene Tape

Product description	Low-noise polypropylene tape for price-sensitive applications
Product data	
~ film	Bi-axial oriented polypropylene film (BOPP)
~ film thickness	25 μ m (ASTMD 3652)
~ adhesive	Pressure-sensitive water based acrylic
~ adhesive thickness	20gsm within acceptable tolerance of +/-6% (ASTMD 3652)
~ colour	Clear
~ roll width	75mm
~ roll length	66mtr
Technical data	
~ initial tack	3.5cm (ASTMD-3121M)
~ peeling adhesion	2.6N/cm (ASTMD-3330M)
~ shear value on steel	>24 hours (ASTMD-3654M)
~ tensile strength	51N/cm (ASTMD-3759)
~ elongation at break	140% (ASTMD-3759)
Storage and use	
~ optimum storage	Maximum 6 months in original packaging and ambient conditions of +22°C and 50% RH Protect from extreme temperatures, humidity and direct sunlight
~ optimum usage	Ambient temperature of +18°C
Packaging data	
~ rolls per case	24
~ case weight	5.6kg

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.