TECHNICAL DATA SHEET



| Product data - tape material - colour - adhesive type - roll width - roll length - tape thickness inc. adhesive - tennile strength - elongation at break - adhesion to steel - temperature resistance Packaging data - rolls per case Self-adhesive polypropylene tape for general packing appleading a | | lene Packing Tape | |
|--|-------------------|--|--------------------------|
| ~ tape material Polypropylene ~ colour Buff ~ adhesive type Solvent ~ roll width 48mm ~ roll length 66mtr ~ tape thickness 30mu ~ total thickness inc. adhesive 50mu Technical data ~ tensile strength 144N/25mm ~ elongation at break 75% ~ adhesion to steel 4.5N/25mm ~ temperature resistance 60°C | king applications | Self-adhesive polypropylene tape for general packing a | Product description |
| tape material colour adhesive type Solvent 48mm roll length tape thickness total thickness inc. adhesive Technical data tensile strength elongation at break adhesion to steel temperature resistance Packaging data | | | Product data |
| ~ colour ~ adhesive type ~ roll width ~ roll length ~ tape thickness ~ total thickness inc. adhesive Technical data ~ tensile strength ~ elongation at break ~ adhesion to steel ~ temperature resistance Buff Solvent 48mm 66mtr 50mu 50mu 144N/25mm 75% 60°C | | Polypropylene | |
| ~ adhesive type ~ roll width ~ roll length ~ tape thickness ~ total thickness inc. adhesive Technical data ~ tensile strength ~ elongation at break ~ adhesion to steel ~ temperature resistance Solvent 48mm 66mtr 30mu 50mu 144N/25mm 75% 60°C | | | • |
| ~ roll width | | | |
| ~ roll length 66mtr ~ tape thickness 30mu ~ total thickness inc. adhesive 50mu Technical data ~ tensile strength 144N/25mm ~ elongation at break 75% ~ adhesion to steel 4.5N/25mm ~ temperature resistance 60°C | | | • • |
| ~ tape thickness 30mu ~ total thickness inc. adhesive 50mu Technical data ~ tensile strength 144N/25mm ~ elongation at break 75% ~ adhesion to steel 4.5N/25mm ~ temperature resistance 60°C | | | |
| ~ total thickness inc. adhesive Technical data ~ tensile strength | | | _ |
| tensile strength elongation at break adhesion to steel temperature resistance Packaging data | | 50mu | - |
| ~ elongation at break 75% ~ adhesion to steel 4.5N/25mm ~ temperature resistance 60°C | | | Technical data |
| ~ adhesion to steel 4.5N/25mm ~ temperature resistance 60°C | | 144N/25mm | ~ tensile strength |
| ~ temperature resistance 60°C Packaging data | | 75% | ~ elongation at break |
| Packaging data | | 4.5N/25mm | ~ adhesion to steel |
| | | 60°C | ~ temperature resistance |
| ~ rolls per case 36 | | | |
| | | 36 | ~ rolls per case |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | İ | |

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.