



# C820 Impulse Heat Sealer

Product description	Desktop impulse heat sealer for fast, professional sealing of PE, PP, PA and PVC foils and thinner, double-coated materials
Product features	<ul style="list-style-type: none"> <li>Adjustable sealing time</li> <li>Manual seal bar closure</li> <li>Sealing wire tensioning unit, for consistent seal</li> <li>Integrated safety film slitting knife</li> <li>One-piece extruded aluminium body for added strength and safety</li> <li>No mechanical switches, for optimum reliability</li> <li>Max. sealing thickness equivalent to 2 layers of 30mu PVC</li> </ul>
Technical data	
~ seal length	820mm
~ seal width	2.5mm
~ max. film width	800mm
~ max. cutting length	800mm
~ max. seal thickness	Polythene - 200mu bag, total 400mu Polypropylene - 80mu bag, total 160mu PVC - 30mu bag, total 60mu
~ dimensions	1020 x 100 x 175mm
Power requirements	
~ supply	230V, 50/60Hz
~ consumption	468w
Spares kit	
~ HA005252	Contains - 1 x element wire, 1 x lower teflon, 1 x upper teflon

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.