## TECHNICAL DATA SHEET



## **DST25V Double Sided Tape**

Product description	Permanently-bonding double sided tape used extensively in the furniture
	industry for mounting PVC profiles.
	Suitable for most substrates including metal, wood, glass and most plastics
Product data	
~ tape material	Unplasticised PVC (uPVC)
~ roll width	25mm
~ roll length	50mtr
~ tape thickness	50mu
~ adhesive	αcrylic
~ liner	90gsm honey glassine
Technical data	
~ loop tack	2.2kg/25mm (FINAT-9)
~ service temperature	- 20°C to + 90°C (short time)
~ shear strength	over 72 hours with 1 kg loading on 25 mm x 25 mm at 25°C (PSTC-7)
~ tensile strength MD	8.0 kg/mm <sup>2</sup>
~ tensile strength TD	4.0 kg/mm <sup>2</sup>
~ peel adhesion	2.4kg/25mm (PSTC-3)
~ elongation MD	120%
~ elongation TD	120%
Packaging data	
~ rolls per case	48
~ case weight	19.65kg
	·

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.