TECHNICAL DATA SHEET



DST4965 Double Sided Tape

Product description	High performance double-sided polypropylene tape used in many industrial
The state of the s	applications including bonding of rubber and EPDM materials, mounting of
	decorative trim, PVC profiles, stainless steel etc.
	, ., ., ., ., ., ., ., ., ., ., ., ., .,
Product data	
~ tape material	clear PET film
~ roll width	50mm
~ roll length	50mtr
~ tape thickness	12mu
~ adhesive	premium acrylic (solvent-based) coated on both sides
~ liner	76mu light pink MOPP film
Technical data	
~ tack	J. Dow No. 16
~ service temperature	- 20°C to + 180°C (short time)
~ shear strength	over 72 hours with 2kg loading on 25mm x 25mm at 25°C (PSTC-7)
~ tensile strength MD	20.0 kg/mm ²
~ tensile strength TD	20.0 kg/mm ³
~ peel αdhesion	1.6kg/25mm (PSTC-3)
~ elongation MD	120%
~ elongation TD	120%
Packaging data	
~ rolls per case	24
~ case weight	17.55kg

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.