## TECHNICAL DATA SHEET



## DST50V Double Sided Tape

Product description	<ul> <li>Permanently-bonding double sided tape used extensively in the furniture industry for mounting PVC profiles.</li> <li>Suitable for most substrates including metal, wood, glass and most plastics.</li> </ul>
Product data ~ tape material ~ roll width ~ roll length ~ tape thickness ~ adhesive ~ liner	Unplasticised PVC (uPVC) 50mm 50mtr 50mu acrylic 90gsm honey glassine
Technical data ~ loop tack ~ service temperature ~ shear strength ~ tensile strength MD ~ tensile strength TD ~ peel adhesion ~ elongation MD ~ elongation TD	2.2kg/25mm (FINAT-9) - 20°C to + 90°C (short time) over 72 hours with 1 kg loading on 25 mm x 25 mm at 25°C (PSTC-7) 8.0 kg/mm <sup>2</sup> 4.0 kg/mm <sup>2</sup> 2.4kg/25mm (PSTC-3) 120% 120%
<ul> <li>rolls per case</li> <li>case weight</li> </ul>	24 19.7kg

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.