TECHNICAL DATA SHEET

ECLN48 Clear Polypropylene Tape

Product description	**BOPP packaging tape**
Product data	
~colour	**clear**
~ tape material	**bi-axial oriented polypropylene film**
~ adhesive	**pressure sensitive water based acrylic**
~ roll width	**48mm**
~ roll length	**66mtr**
Technical data	
~ film thickness	**25mu (ASTMD 3652)**
~ coating weight	**17gsm (ASTMD 3652)**
~ coating weight tolerance	**within accepted level of +/- 6%**
~ initial tack	**4.0cm (ASTMD-3121M)**
~ peeling adhesion	**6.80N/inch (ASTMD-3759)**
~ elongation at break	**120% (ASTMD-3759)**
~ application temperature limits	**+15˚C to +65˚C**
Recommended storage	
~ maximum storage period	**6 months**
~ optimum temperature	**+22˚C**
~ optimum humidity	**50%**
~ optimum environment	**Protect from direct sunlight and extremes of temperature and humidity and protect the opened pack from dust and other contamination**
Packaging data	
~ rolls per case	**36**
~ case weight	**5.9kg**

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.