TECHNICAL DATA SHEET

HLCA-19B Hook and Loop Coins, Black

Product description	Pre-cut circles of self-adhesive hook and loop tape material
	Used extensively in graphics/display and assembly applications and on a variety of surfaces including paper, wood, polythene, metal, glass, plastic (excluding plasticised PVC) etc.
	Supplied as a two-roll set (one hooked tape, one looped tape)
Product data	
~ coin diameter	19mm
~ tape colour	Black
~ adhesive type	Hotmelt
~ coins per roll	125
~ roll weight	15kg
Technical data	
~ adhesion (hook tape)	646 minutes (PSTC-7)
~ adhesion (loop tape)	686 minutes (PSTC-7)
~ shear adhesion fail level	60˚C (PSTC-7)
~ peel adhesion @ 180˚C (hook)	1.34kg/cm² (PSTC-1)
~ peel adhesion @ 180˚C (loop)	1.38kg/cm² (PSTC-1)
~ shear strength	0.85kg/cm² (CNS 12649 L3227)
~ peel strength	200g/cm (CNS 12649 L3227)
~ tear strength	2kg (ASTM D2261)
~ usage limitations	Not recommended for direct exposure to sunlight or UV
	Not suitable for use on surfaces contaminated by humidity, dust, oil etc.
	Application and performance temperature from +5˚C to +40˚C

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.