

HQS80-15-12

HIGH SPEED AUTOMATIC STRAPPING MACHINE

(optimax)



additional operator-friendly features.





HQS80-15-12

HIGH SPEED AUTOMATIC STRAPPING MACHINE

1-45K

240V

167 kg

Features include:

- > German brushless motor technology
- > Reliable, low-maintenance strapping head
- > Tool-free access to strapping head and strap guides
- > Compatible with 12mm polypropylene strap
- > Automatic strap loop ejector for accidental cycle activation
- > Automatic strap feed for load-and-go reel changes
- > Adjustable table height (820-920mm)
- > Lockable swivel castors



Suitable for use with polypropylene strapping



Strapping speed/ cycle rate



Heat weld seal no need for metal seals



Suitable for carton strapping applications



Total machine weight





mechanical strapping head





strap guides



Waist high quick coil change

Ergonomic Cycle Initiation

The operating control panel is located on upper side of the machine for easy access. The power cord is also located at the top of the arch to avoid damage when moving the machine. Front foot bar switch. Ergonomic design and user-friendly.

Specifications

Machine Weight: Machine Dims w x d x h (mm): 1200 x 652 x 1425-1525 Arch Size w x h (mm): Max Package Weight: Max Package Size w x h (mm): 600 x 450 Strap Widths (mm): Min/Max PP Thickness: Strap Inner Core Dims: Min/Max Tension: Speed/Cycle: Power Requirement: Power Consumption:

Options

- > Photo-eye switch
- > Rear foot bar switch
- > Stainless steel frame

650 x 500 70 kg 12mm 0.45mm - 0.65mm 200mm 1-45 kg (Strap Dependent) 60 straps/min (@50Hz if applicable) 240v 50Hz 1PH 500w

Strapping tension

Power requirements

Suitable for engineering

industry applications

Adjustable leg/

table height

range



