

HQS80-15

HIGH SPEED AUTOMATIC STRAPPING MACHINE



The HQS80-15 is an innovative, world class, high speed automatic strapping machine. It is equipped with all industry-standard and additional operator-friendly features.





HQS80-15

HIGH SPEED AUTOMATIC STRAPPING MACHINE

Features include:

- > German brushless motor technology
- > Reliable, low-maintenance strapping head
- > Tool-free access to strapping head and strap guides
- > Compatible with 5mm, 6mm, and 9mm polypropylene strap
- > Automatic strap loop ejector for accidental cycle activation
- > Automatic strap feed for load-and-go reel changes
- > Adjustable table height (820-920mm)
- > Lockable swivel castors



PP Suitable for use with polypropylene strapping

1-32Kg Strapping tension range

65/min Strapping speed/ cycle rate

240V 50Hz Power requirements

Heat weld seal - no need for metal seals

Adjustable leg/ table height

Suitable for carton strapping applications

Suitable for engineering industry applications

157Kg Total machine weight



Auto loop ejector




Robust & compact mechanical strapping head



Free access to strap guides



Waist high quick coil change



Ergonomic Cycle Initiation
The operating control panel is located on upper side of the machine for easy access. The power cord is also located at the top of the arch to avoid damage when moving the machine. Front foot bar switch. Ergonomic design and user-friendly.

Specifications

Machine Weight:	157 kg
Machine Dims w x d x h (mm):	840 x 652 x 1325-1425
Max Package Weight:	70 kg
Strap Widths (mm):	5-6-9
Min/Max PP Thickness:	0.45mm - 0.65mm
Min/Max Tension:	1-32 kg (Strap Dependent)
Speed/Cycle:	65 straps/min (@50Hz if applicable)
Power Requirement:	240v 50Hz
Power Consumption:	300w

Options

- > Photo-eye switch
- > Rear foot bar switch
- > Stainless steel frame

