TECHNICAL DATA SHEET

Tegrabond® K7020C76W-90GSO Water Activated Tape

Product description	**Heavy duty kraft paper tape with water activated adhesive.**
Product data	
~ paper	**90gsm white kraft**
~ adhesive	**22-24gsm waxy maize starch based remoistenable adhesive**
	on outside face of tape when on roll
~ roll width	**70 mm**
~ roll length	**200 mtr**
~ internal core diameter	**76 mm**
Technical data	
~ moisture content	**7.0% (ISO-287)**
~ pH level	**6.5 (DIN 53124)**
~ tensile strength MD	**110 kN.m/kg (ISO-1924)**
~ tensile strength CD	**40 kN.m/kg (ISO-1924)**
~ burst	**435 kPa (ISO-2758)**
~ burst index	**4.8 kPa.m²/g (ISO-2758)**
~ COBB-60 (Anv)	**29 gsm - PS (ISO-535)**
~ thickness	**0.117 mm (UNE 57103)**

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.