## TECHNICAL DATA SHEET



## KR7015B-IMPCA Tegrabond® Message Tape

Product description	Natural kraft carton tape with three-way fibreglass reinforcement and water
	activated adhesive on inside tape face.
	Used for top and bottom carton closure sealing, adhering well to recycled
	carton material and light-medium cartons.
	Printed with 'Important Caution' message
	1 5
Product data	
~ roll width	70mm
~ roll length	152mtr
~ roll weight	1.44kg
Construction	
~ top ply	33gsm natural kraft
~ bottom ply	40gsm natural kraft
~ adhesive	24gsm chemically grafted starch-based copolymer
~ MD reinforcement	839g (1-1-1-1/1-1-1) 110 fibreglass per 70mm at 15mm CD spacing
~ CD reinforcement	671g (1-1-1) 150 fibreglass, 27.5mm spacing at 44° angle
~ total base weight	125gsm
~ caliper	144mu
Technical data	
~ MD tensile strength	284N/cm <sup>2</sup>
~ CD tensile strength	120N/cm <sup>2</sup>
Adhesion	(using water heated to recommended 43.3°C)
~ Fipago 2/0	58
~ Fipago 2/1	81 83
~ Fipago 5/0	92
~ Fipago 15/0 ~ McClaurin	81
	01
Packaging data	
~ rolls per case	6
~ case height	230mm
~ case length	344mm
~ case width	182mm
~ case weight	8.6kg
All information and recommendations are provided to the best o	of our knowledge, on the basis of our practical experience.