TECHNICAL DATA SHEET

# PCT75-W White Cloth Tape

| | |
|---|---|
| **Product description** | Self-adhesive polycloth duct tape |
| | Used for sealing, insulation, packaging, masking and repair |
| | General purpose interior and exterior use |
| | |
| **Product data** | |
| ~ roll width | 75mm |
| ~ roll length | 50mtr |
| ~ material | Woven polyester and coated cotton blended with LDPE |
| ~ adhesive | Synthetic rubber |
| | |
| **Technical data** | |
| ~ total thickness | 0.17mm (+/- 5%) |
| ~ adhesion to steel | 18N per 25mm |
| ~ tensile strength | 75N per 25mm |
| ~ rolling ball tack | > 12 (ball no.) |
| ~ holding power | > 3 hours |
| ~ service temp. range | -15 C to +60 C |
| | |
| **Application** | Optimum adhesion is achieved after a 24 hour bonding period in a |
| | constant ambient temperature of +23 C if: |
| | ~ surfaces are clean, and free from grease and dust |
| | ~ the tape is applied at temperatures between 0 C and +35 C |
| | ~ contact with the exposed adhesive is avoided |
| | ~ maximum pressure is used during application |
| | |
| **Storage and shelf life** | Kept in clean, dry, well-ventilated conditions and an ambient temperature |
| | of +10 C to +30 C, the shelf life will be a minimum of 12 months |
| | |
| **Packaging data** | |
| ~rolls per case | 16 |
| ~ case weight | 14kg |

*All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.*
*Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.*
*The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.*