

## PLO-35 Polyolefin Shrink Film

Product description	Polyolefin shrink film for use with impulse heat sealers, centrefolded to enable
	single-action sealing on L-bar type sealers.
	Polyolefin id approved for food industry and coldstore use, and doesn't
	discolour with age or become brittle in low temperatures.
Product data	
~ film thickness	15.0mu
~ unfolded film width	700mm
~ folded film width	350mm
~ roll length	1335mtr
~ core internal diameter	76.2mm
~ nett roll weight	13.6kg
Technical data	
~ yield	72.5m²/kg
~ gloss at 85° angle	135%
~ haze	1.50%
~ shrinkage at 93°C	20%
~ shrinkage at 120°C	55%
~ seal strength	52MPa
~ tear propagation	13g
~ WVTR*	14gsm/24hr @ 95% RH, 35°C
~ oxygen permeability	7,000cm <sup>3</sup> /m <sup>2</sup> /24hr @23°C, 1 atm
oxygen permeability	
	* water vapour transmission rate

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.