## TECHNICAL DATA SHEET



## **PT60G Polyester Strapping**

| Product description   | E |
|-----------------------|---|
|                       |   |
| Product data          |   |
| ~ raw material        | 1 |
| ~ colour              | g |
| ~ texture             | е |
| ~ width               | 1 |
| ~ thickness           | 1 |
| ~ length              | 1 |
| ~ core                | 4 |
|                       |   |
| Technical data        | _ |
| ~ break strain        | 7 |
| ~ elongation at break | 1 |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |
|                       |   |

Extruded polyester for high strength and elasticity

100% PET (homopolymer) green embossed 15.5mm (15.7 - 15.8mm) 1.1mm (1.06 - 1.14mm) 1,000mtr 406 x 150mm cardboard

720kg (700 - 740kg) 12-14%