TECHNICAL DATA SHEET



RSK16 Medium Duty Combination Strapping Tool

 construction aluminimum alloy, part painted 465 x 135 x 19mm 4.8kg Technical data max. strap width min. strap thickness max. strap thickness max. strap thickness compatible seals Packaging data dimensions (inc. carton) qty. per outer carton 500 x 500 x 360mm Aluminimum alloy, part painted 465 x 135 x 19mm 4.8kg Technical data 0.4mm 0.9mm 200kg 16mm serrated (Safeguard® SER16-SG recommended) 	Product description	Manually operated tensioner, sealer and cutter for use with 16mm
Product data ~ construction Aluminimum alloy, part painted ~ overall dimensions 465 x 135 x 19mm 4.8kg Technical data ~ max. strap width		
 overall dimensions weight 465 x 135 x 19mm 4.8kg Technical data max. strap width min. strap thickness max. strap thickness max. strap thickness o.9mm max. strapping tension compatible seals 16mm serrated (Safeguard® SER16-SG recommended) Packaging data dimensions (inc. carton) qty. per outer carton outer carton dimensions 500 x 500 x 360mm 		No manual dajustment is needed when changing the strap thickness
~ overall dimensions	Product data	
- weight 4.8kg Technical data - max. strap width - min. strap thickness - max. strap thickness - max. strap thickness - max. strapping tension - compatible seals 16mm serrated (Safeguard® SER16-SG recommended) Packaging data - dimensions (inc. carton) - qty. per outer carton - outer carton dimensions 4.8kg 16mm 4.8kg	~ construction	
Technical data ~ max. strap width ~ min. strap thickness ~ max. strap thickness ~ max. strapping tension ~ compatible seals Packaging data ~ dimensions (inc. carton) ~ qty. per outer carton 6 ~ outer carton dimensions 16mm 16mm 20.4mm 200kg 16mm serrated (Safeguard® SER16-SG recommended) 465 x 135 x 25mm 6 ~ outer carton dimensions 500 x 500 x 360mm	~ overall dimensions	465 x 135 x 19mm
 max. strap width min. strap thickness max. strap thickness max. strapping tension compatible seals Packaging data dimensions (inc. carton) qty. per outer carton outer carton dimensions 16mm 0.9mm 200kg 16mm serrated (Safeguard® SER16-SG recommended) 465 x 135 x 25mm qty. per outer carton 500 x 500 x 360mm 	~ weight	4.8kg
 min. strap thickness max. strap thickness max. strapping tension compatible seals Packaging data dimensions (inc. carton) qty. per outer carton outer carton dimensions 0.4mm 200kg 16mm serrated (Safeguard® SER16-SG recommended) 465 x 135 x 25mm qty. per outer carton 500 x 500 x 360mm 	Technical data	
 max. strap thickness max. strapping tension compatible seals Packaging data dimensions (inc. carton) qty. per outer carton outer carton dimensions 0.9mm 16mm serrated (Safeguard® SER16-SG recommended) 465 x 135 x 25mm 6 outer carton dimensions 500 x 500 x 360mm 	~ max. strap width	16mm
 max. strapping tension compatible seals Packaging data dimensions (inc. carton) qty. per outer carton outer carton dimensions 200kg 16mm serrated (Safeguard® SER16-SG recommended) 465 x 135 x 25mm 6 500 x 500 x 360mm 	~ min. strap thickness	0.4mm
~ compatible seals 16mm serrated (Safeguard® SER16-SG recommended) Packaging data ~ dimensions (inc. carton) 465 x 135 x 25mm ~ qty. per outer carton 6 ~ outer carton dimensions 500 x 500 x 360mm	~ max. strap thickness	0.9mm
Packaging data ~ dimensions (inc. carton) 465 x 135 x 25mm ~ qty. per outer carton 6 ~ outer carton dimensions 500 x 500 x 360mm	~ max. strapping tension	200kg
 dimensions (inc. carton) 465 x 135 x 25mm qty. per outer carton outer carton dimensions 500 x 500 x 360mm 		16mm serrated (Safeguard® SER16-SG recommended)
 dimensions (inc. carton) 465 x 135 x 25mm qty. per outer carton outer carton dimensions 500 x 500 x 360mm 	Packaging data	
~ outer carton dimensions 500 x 500 x 360mm		465 x 135 x 25mm
	~ qty. per outer carton	6
~ full outer carton weight 29.6kg	~ outer carton dimensions	500 x 500 x 360mm
	~ full outer carton weight	29.6kg
	_	