

RSW6

ROBOTIC PALLET STRETCH WRAPPER



The Optimax® RSW6 Robotic Pallet Stretch Wrapper helps to maximise despatch operation efficiency and productivity.



RSW6

ROBOT PALLET STRETCH WRAPPER

The RSW6 offers versatile, mobile automated pallet wrapping with trusted Optimax technology and build quality.

Features include:

- > No maximum pallet weight, width or depth
- > Minimal clearance required around pallet
- > Easily relocated to where wrapping required
- > Powered film pre-stretching minimises film usage and creates a more stable pallet load
- > Password-protected touchscreen control panel features
 - Independently adjustable top and bottom wrapping count and tension
 - Two power pre-stretch ratios offering 230% and 300% film length increase
 - Adjustable cart rotation speed
 - Adjustable film carriage speed
- > Film carriage is easily reloaded and features an anti-drop mechanism for improved safety
- > One-way idling roller prevents entanglement in the event of film breakage and facilitates film re-feed
- > Soft-wrapping feature protects pallet contents from damage due to uneven film tension at corners
- > Automatic photocell pallet height detection
- > Automatic end of cycle film cutting
- > High capacity, zero maintenance batteries deliver up to 300 pallet wraps per charge



Specifications

Batteries:	2x 12v100Ah non-maintenance lead acid
Power consumption:	0.7kW
Dimensions:	1175 x 1758 x 2570mm
Max. wrapping height:	2200mm
Min. wrapping height:	450mm
Cart rotation speed:	20-90mtr/min.
Film carriage speed:	1-5mtr/min.
Min. pallet size:	600 x 600mm
Operation radius:	1150mm from edges of load or pallet
Wraps per charge:	>300 pallets
Nett weight:	292kg

