

ST455

COMBINED L-SEALER & SHRINK TUNNEL



The Optimax® ST455 maximises productivity and provides faster output by combining sealing and shrinking functions in one unit.



ST455

COMBINED L-SEALER & SHRINK TUNNEL

The ST455 provides consistent, optimised heat sealing and shrinking in one unit, whilst increasing productivity and despatch operation efficiency.



Features include:

- > Separate sealer and shrink tunnel for faster throughput
- > Powerful, high-capacity heat sealing
- > Extendable weld cooling time
- > The ST455 requires a 3.5 to 4.5kg/cm² compressed air supply.

Please contact our technical service centre for more information.



Variable temperature control



Simple to operate control panel

Specifications

- | | |
|---------------------------------|---------------------------------|
| > Power supply: | 400V, 50Hz |
| > Max. power consumption: | 9kW |
| > Sealing dimensions | 400 x 550mm (D x L) |
| > Tunnel inlet dimensions: | 400 x 200mm (W x H) |
| > Working plate height: | 900mm |
| > Max. packing height: | 150mm |
| > Machine dimensions: | 2570 x 870 x 1600mm (L x W x H) |
| > Max. dimensions of film roll: | 600mm x Ø300mm |
| > Machine weight: | 400kg |

