

TILTW Tiltwatch Monitors

Product description	<p>Adhesive-backed single-use monitor that activates when the package, crate or pallet to which it has been attached has been subjected to tilt exceeding a predetermined angle.</p> <p>Each monitor will detect tilt in a single plane; if detection of sideways and forward-backward tilt is required, two monitors should be mounted on vertical planes that are at right angles to each other.</p>
Product application	<p>The Tiltwatch monitor is primed as soon as the release liner is removed from the adhesive backing; care should be taken to hold the monitor at the correct angle whilst it is being applied to prevent accidental activation.</p> <p>The monitor may be secured to the consignment using the adhesive backing and/or with small screws, nails or staples using the holes provided, for rough or adhesion-resistant surfaces (the backing must nevertheless be removed to prime the monitor, even if the adhesive backing is not to be used).</p> <p>Each Tiltwatch monitor is supplied with an adhesive companion label to warn that tilt is being monitored and to encourage correct handling.</p>
Product data	<p>Rigid polystyrene housing, stainless steel indicator</p>
~ construction	
~ dimensions	67 x 74 x 4.8mm
~ adhesive	High tack pressure-sensitive acrylic
~ activation angle	80° from vertical (+/- 5%)
~ humidity tolerance	0% - 100%
~ temperature tolerance	-40°C to +60°C
~ shelf life	24 months

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.