

# TMS300

## SEMI-AUTO STRAPPING MACHINE



A reliable and ruggedly built semi-auto strapping machine with a fully enclosed cabinet that protects the operator and reduces airborne contamination of the mechanism and strapping reel.





# TMS300

## SEMI-AUTO STRAPPING MACHINE

### Features include:

- > Simple use and maintenance
- > Safety interlocked stainless steel top plate
- > Enclosed cabinet
- > Fixed/swivel castors
- > Manual strap tension adjustment
- > Reliable, energy-efficient operation
- > Compatible with 200mm/280mm core strapping



**PP** Suitable for use with polypropylene strapping

**15-45Kg** Strapping tension range

**3 secs** Strapping speed/ cycle rate

**240V 50Hz** Power requirements

**Heat weld seal** - no need for metal seals

**Suitable for engineering industry applications**

**Suitable for carton strapping applications**

**100Kg** Total machine weight



The TMS300 employs a reliable mechanical sealing head



Simple to use electronic control panel



Manual strap tension control

### Specifications

Machine Weight:	100 kg
Machine Dims w x d x h (mm):	920 x 595 x 785
Max Package Weight:	120 kg
Strap Widths (mm):	9-16
Min/Max PP Thickness:	0.5mm - 0.75mm
Min/Max Tension:	15-45 kg (Strap Dependent)
Speed/Cycle:	3 secs (@50Hz if applicable)
Power Requirement:	240v 50Hz
Power Consumption:	250w

### Options

- > Safety switch under table top
- > Adjustable cooling time (0-2 sec.)

