

TP4104 Polythene Industrial Tarpaulins

Product description

High quality, fully eyeletted, durable industrial tarpaulins suitable for outside and inside storage applications

Product material

- ~ basic fabric
- ~ composition fabric
- ~ lacquering
- ~ material weight
- ~ product dimensions
- ~ product weight

100% polythene (DIN EN ISO 2060) raw 49 gsm, coating 41 gsm 1/0 90gsm (DIN EN ISO 2286-2) 8000 x 5000mm 3.45kg

Technical data

- ~ breaking strength warp
- ~ breaking strength weft
- ~ tear strength warp
- ~ tear strength weft
- ~ adhesion
- ~ temperature resistance
- ~ lightfastness

4,000 N/5 cm (DIN 53 354) 3,400 N/5 cm (DIN 53 354) 580 N (DIN 53 363) 480 N (DIN 53 363) 100 N/5 cm (DIN 53 357) between -30°C and +70°C (DIN EN1876-2) 7-8 (Anti-UV) (DIN EN ISO 877)

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.