TECHNICAL DATA SHEET

TP4106 Polythene Industrial Tarpaulins

Product description	High quality, fully eyeletted, durable industrial tarpaulins suitable for outside and inside storage applications
Product material	
~ basic fabric	100% polythene (DIN EN ISO 2060)
~ composition fabric	raw 49 gsm, coating 41 gsm
~ lacquering	1/0
~ material weight	90gsm (DIN EN ISO 2286-2)
~ product dimensions	12000 x 8000mm
~ product weight	8.45kg
Technical data	
~ breaking strength warp	4,000 N/5 cm (DIN 53 354)
~ breaking strength weft	3,400 N/5 cm (DIN 53 354)
~ tear strength warp	580 N (DIN 53 363)
~ tear strength weft	480 N (DIN 53 363)
~ adhesion	100 N/5 cm (DIN 53 357)
~ temperature resistance	between -30^{0}C and +70^{0}C (DIN EN1876-2)
~ lightfastness	7-8 (Anti-UV) (DIN EN ISO 877)

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.