

TRS600

AUTOMATIC STRAPPING MACHINE



High-volume carton and package strapping machine with hands-free operation for maximum productivity, available in a selection of arch sizes.



TRS600

AUTOMATIC STRAPPING MACHINE

TRS600-9

for use with 9mm polypropylene

TRS600-12L

for use with 12mm polypropylene

TRS600-12

for use with 12mm polypropylene

Features include:

- > External manual strap tension adjustment
- > Up to 27 cycles per minute
- > Activation by foot pedal, console button or ball switch
- > Short-feed sensor to prevent strap misfeed
- > Reliable control head construction



PP Suitable for use with polypropylene strapping

10-70Kg Strapping tension range

2.2 secs Strapping speed/ cycle rate

240V 50Hz Power requirements

Heat weld seal - no need for metal seals

Adjustable leg/ table height

Suitable for carton strapping applications

Suitable for engineering industry applications

280Kg Total machine weight



The TRS600 employs a reliable mechanical sealing head



Footpedal activation



Manual strap tension control

Specifications

Machine Weight:	280 kg
Machine Dims w x d x h (mm)	1430 x 620 x 1540mm
TRS600-9, TRS600-12:	1630 x 620 x 1740mm
TRS600-12L:	
Max Package Weight:	100 kg
Strap Widths (mm):	9-12
Min/Max PP Thickness:	0.55mm - 0.75mm
Min/Max Tension:	10-70 kg (Strap Dependent)
Speed/Cycle:	2.2 secs (@50Hz if applicable)
Power Requirement:	240v 50Hz
Power Consumption:	1.2kw

Options

- > Short feed sensor
- > Stainless steel frame

