

Tegracheck[®] TSLB4040 Non-Transfer Labels

Product Description	Partial delamination of the label structure occurs if disturbed, creating a clear indicator of tamperage whilst maintaining adhesion to metal, glass and high energy plastic surfaces. No residue on removal makes this product ideal for reuseable packaging and delicate surfaces.
Product applications	Sealing of reusable packaging containers and airline/hospital trolleys Temporary bonding of vehicle and aircraft doors. Deterrence of unauthorised access to restricted areas. Protecting electronic or mechanical components against warranty invalidation.
Product data	
~ colour	blue, with black surface print
~ label size	40mm diameter
~ base film material	PET
~ liner	White double PE, single silicon glassine paper
~ total thickness	0.087 - 0.095mm
~ quantity per roll	250
Technical data	
~ 180° peel adhesive	600 - 1200g/25mm, 5.86 - 11.71N/25mm (PSTC-1)
~ initial tack	< 100mm (PSTC-6 - #14 ball)
~ holding power, ambient*	> 72 hours, 0.5kg/625mm ² (PSTC-7)
~ holding power @ +60°C	> 24 hours, 0.5kg/625mm ² (PSTC-7)
~ VOID temperature	-10°C to +40°C (recommended operating temperature +10°C to +35°C)
* Laboratory environment	
~ temperature	+18°C to +28°C
~ humidity	45 - 65% RH

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.