TECHNICAL DATA SHEET



Tegracheck® TSLB8540 Non-Transfer Labels

Product Description	Partial delamination of the label structure occurs if disturbed, creating a clear
Troduct Bescription	indicator of tamperage whilst maintaining adhesion to metal, glass and high
	energy plastic surfaces. No residue on removal makes this product ideal for
	reuseable packaging and delicate surfaces.
	- Caronara Pannaging and annual carriages
Product applications	Sealing of reusable packaging containers and airline/hospital trolleys
	Temporary bonding of vehicle and aircraft doors.
	Deterence of unauthorised access to restricted areas.
	Protecting electronic or mechanical components against warranty invalidation.
Product data	
~ colour	blue, with black surface print
~ label size	85 x 40mm
~ base film material	PET
~ liner	White double PE, single silicon glassine paper
~ total thickness	0.087 - 0.095mm
~ quantity per roll	250
Technical data	
~ 180° peel adhesive	600 - 1200g/25mm, 5.86 - 11.71N/25mm (PSTC-1)
~ initial tack	< 100mm (PSTC-6 - #14 ball)
~ holding power, αmbient*	> 72 hours, 0.5kg/625mm² (PSTC-7)
~ holding power @ +60°C	> 24 hours, 0.5kg/625mm² (PSTC-7)
~ VOID temperature	-10°C to +40°C (recommended operating temperature +10°C to +35°C)
* Laboratory environment	
~ temperature	+18°C to +28°C
~ humidity	45 - 65% RH
·	