TECHNICAL DATA SHEET

XTEGRA®

Tegracheck® TSLR4040 Total Transfer Labels

Product Description	**Tamper evident labels with an OPEN VOID printed residue that cannot be easily removed and sends a clear alert if the label has been disturbed or removed.**
Product applications	**Ideal for presentation and consignment packaging of valuable items.**
Product data	
~ colour	**red, with black surface print**
~ label size	**40mm diameter**
~ base film material	**PET**
~ liner	**White double PE, single silicon glassine paper**
~ total thickness	**0.095 - 0.105mm**
~ quantity per roll	**250**
Technical data	
~ 180° peel adhesive	**20 - 60g/25mm, 0.20 - 0.59N/25mm (PSTC-1)**
~ initial tack	**< 100mm (PSTC-6 - #14 ball)**
~ holding power, ambient*	**> 24 hours, 0.5kg/625mm² (PSTC-7)**
~ holding power @ +60˚C	**> 3 hours, 0.5kg/625mm² (PSTC-7)**
~ VOID temperature	**-10˚C to +40˚C (recommended operating temperature +10˚C to +35˚C)**
*** Laboratory environment**	
~ temperature	**+18˚C to +28˚C**
~ humidity	**45 - 65% RH**

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.