

## TW60AWI Message Tape

Product description	White low-noise polypropylene tape printed with high-visibility warning message
Product data	
~ printed message	AWAITING INSPECTION
~ backing film	Bi-axial oriented polypropylene
~ film thickness	28mu (ASTM D3652)
~ adhesive type	Pressure sensitive, water based acrylic
~ adhesive weight	20gsm +/-6% acceptable tolerance (ASTM D3652)
~ tape width	50mm
~ tape length	66mtr
Technical data	
~ initial tack	3.5cm (ASTM D3121M)
~ peeling adhesion	6.3N/inch (ASTM D3330M)
~ shear value on steel	>24 hours (ASTM D3654M)
~ tensile strength	75.0N/inch (ASTM D3759)
~ elongation at break	105% (ASTM D3759)
Storage & application data	
~ temperature	Optimum +25°C, minimum +15°C, maximum +65°C
~ optimum humidity	65%
~ optimum storage	< 6 months, away from extreme temperature/humidity and direct sunlight
~ application temperature	Between +18°C and +65°C

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.