TECHNICAL DATA SHEET

TW60TWU Message Tape

Product description	**White low-noise polypropylene tape printed with high-visibility warning message**
Product data	
~ printed message	**THIS WAY UP**
~ backing film	**Bi-axial oriented polypropylene**
~ film thickness	**28mu (ASTM D3652)**
~ adhesive type	**Pressure sensitive, water based acrylic**
~ adhesive weight	**20gsm +/-6% acceptable tolerance (ASTM D3652)**
~ tape width	**50mm**
~ tape length	**66mtr**
Technical data	
~ initial tack	**3.5cm (ASTM D3121M)**
~ peeling adhesion	**6.3N/inch (ASTM D3330M)**
~ shear value on steel	**>24 hours (ASTM D3654M)**
~ tensile strength	**75.0N/inch (ASTM D3759)**
~ elongation at break	**105% (ASTM D3759)**
Storage & application data	
~ temperature	**Optimum +25˚C, minimum +15˚C, maximum +65˚C**
~ optimum humidity	**65%**
~ optimum storage	**< 6 months, away from extreme temperature/humidity and direct sunlight**
~ application temperature	**Between +18˚C and +65˚C**

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.