TECHNICAL DATA SHEET

YELMP48 Polypropylene Machine Tape

Product description	Polypropylene packing tape with solvent-free hotmelt adhesive.
	High-capacity roll for use with case taping machines.
Product data	
~ colour	Yellow
~ roll width	48mm
~ roll length	990mtr
~ film thickness	Average 25mu (ASTM D3652)
~ adhesive weight	Average 16gm² (ASTM D3652)
Technical data	
~ initial tack	Average 4.0cm by 14# rolling ball (ASTM D3121)
~ peel adhesion on steel	Average 1.86N/cm² (ASTM D3330)
~ holding power on steel	Average >48hours (ASTM D3654)
~ tensile strength (MD	Average 13.18N/cm² (ASTM D3759)
~ elongation at break	Average 105%
~ application temperature	+15˚C to +60˚C
~ storage temperature	+5˚C to +50˚C
Packaging data	
~ rolls per case	6
~ case weight	12.6kg

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.
Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.
The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.